



EN 1504-2:2004

14

1020

ДЕКЛАРАЦИЯ ЗА ЕКСПЛОАТАЦИОННИ ПОКАЗАТЕЛИ

SikaSeal®-210 Migrating

02	07	01	01	001	0	000249	1180
----	----	----	----	-----	---	--------	------

1. Тип на продукта:

Уникален идентификационен код на типа продукт:

SikaSeal®-210 Migrating

2. Тип, партиден номер или сериен номер, или друг елемент, който позволява да се идентифицира строителния продукт съгласно изискванията на член 11, параграф 4:

Партиден № виж етикета на продукта

3. Предвидена употреба или употреби на строителният продукт в съответствие с приложимата хармонизирана спецификация, както е предвидено от производителя:

1-компонентен хидроизолиращ разтвор, съдържащ проникващи кристализиращи добавки, уплътняващи бетона срещу проникване на вода.

Продукт за повърхностна защита - покритие. Предназначение - Таблица ZA.1e от EN 1504-2:2004. Принцип 2, Метод 2.2 съгласно EN 1504-9:2008.

**В съответствие с Анекс ZA
таблица ZA.3a.**

4. Име, регистрирано търговско наименование или регистрирана търговска марка и адрес за контакт на производителя съгласно изискванията на член 11, параграф 5:

**Sika®
Sika CZ, s.r.o.
Bystrcka 1132/36
CZ 624 00 Brno
Чехия**

5. Адрес за контакти:

Когато е приложимо, име и адрес за контакт на упълномощения представител, чието пълномощие включва задачите, посочени в член 12, параграф 2:

Не е приложимо (виж 4)



6. AVCP:

Система или системи за оценяване и проверка на постоянството на експлоатационните показатели (AVCP) на строителния продукт, както са изложени в приложение V:

EN 1504-2:2004 → Система 2+

7. Нотифициран орган (hEN):

В случай на декларация за експлоатационни показатели относно строителен продукт, обхванат от хармонизиран стандарт:

1020
 Нотифицираният орган по сертификация на производствен контрол № 1020, Technicky a zkušební ústav Praha, s.p. извърши първоначална проверка на производствената площадка и производствения контрол, осъществявайки постоянен надзор, оценка и анализ на производствения контрол и издаде сертификат за съответствие на производствения контрол в предприятието (FPC) 020025682.

8. Нотифициран орган (ETA):

В случай на декларация за експлоатационни показатели относно строителен продукт, за който е издадена европейска техническа оценка:

Не е приложимо (виж 7)

9. Декларирани експлоатационни показатели

Съществени характеристики	Експлоатационни показатели	Метод на изпитване	Хармонизирана техническа спецификация
Линейно съсъхване	NPD	EN 12617-1	EN 1504-2: 2004
Коеф. на топлинно разширение	NPD	EN 1770	
Адхезия чрез изпитване чрез решетъчни нарязи	NPD	EN ISO 2409	
Пропускливост на водни пари	Клас I	EN ISO 7783-1	
Капилярна абсорбция на вода и водопропускливост	$w < 0.1 \text{ kg}/(\text{m}^2 \times \text{h}^{0.5})$	EN 1062-3	
Адхезия след изпитване за термична съвместимост	NPD	EN 13687-2	
Устойчивост на напукване	NPD	EN 1062-7	
Адхезионна якост (pull-off)	$\geq 1.0 (0.7) \text{ N}/\text{mm}^2$	EN 1542	
Реакция на огън	A1	EN 13501-1	
Съпротивление при хлъзгане/приплъзване	NPD	EN 13036-4	
Изкуствено стареене	NPD	EN 1062-11	
Електрическо съпротивление	NPD	EN 1081	
Опасни вещества	Виж MSDS	-	

NPD - Неустановени експлоатационни показатели



10. Декларация

Експлоатационните показатели на продукта, посочени в точки 1 и 2, съответстват на декларираните експлоатационни показатели в точка 9.

Настоящата декларация за експлоатационни показатели се издава изцяло на отговорността на производителя, посочен в точка 4.

Подписано за и от името на производителя от:

Eng. Jaroslav Leischner
QMS and EHS Manager

Eng. Zdenek Bilek, MBA
General Manager Sika CZ

Brno, 15 Април 2014

Информация за екология, здравеопазване и безопасност (REACH)

За информация и съвети относно безопасното транспортиране, съхранение и отвеждане на химическите продукти, моля обърнете се към Листа с данни за безопасност, който съдържа физични, екологични, токсикологични и други свързани с безопасността данни.

REACH

Наредба на Европейския съюз за химикалите и тяхната безопасна употреба (REACH: EC 1907/2006)

Този продукт е изделие по смисъла на член 3 от наредбата на (ЕС) № 1907/2006. Той не съдържа вещества, които може да се отделят от изделието при нормални и разумно предвидими условия на употреба. Лист с данни за безопасност съгласно член 31 на същата наредба не е необходим при пускането на продукта на пазара, транспорта или употребата му. За безопасна употреба следвайте инструкциите дадени в Листа с технически данни на продукта.

Базирано на нашите текущи познания, този продукт не съдържа SVHC (вещества, предизвикващи сериозно безпокойство) описани в Annex XIV на REACH наредбата или вещества от списъка с кандидатите, публикуван от Европейската Агенция за химикалите в концентрация над 0.1%.

Правна информация:

Информацията и по-специално препоръките за приложение и използването на продуктите на Sika, са дадени добронамерено и се базират на текущите познания и опит на Sika с продуктите при условия на правилно съхранение, боравене и използване в нормални условия в съответствие с препоръките на Sika. На практика разликите в материалите, основите и действителните условия на обекта са такива, че не може да се гарантира пригодността за определена цел, нито да възникнат законови задължения от настоящата информация, нито от писмени препоръки или други съвети. Потребителят на продукта трябва да провери пригодността на продукта към поставените изисквания и цели. Sika запазва правото да променя характеристиките на своите продукти. Правата на собственост на трети страни следва да бъдат спазвани. Всички поръчки се приемат съгласно нашите текущи условия за продажба и доставка. Потребителите са длъжни винаги да правят справка с последното издание на Листа с технически данни за съответния продукт, копия от който се предоставят по заявка.



За допълнителна информация:

„Сика България“ ЕООД
бул. „Ботевградско шосе“ № 247
1517, София
www.sika.bg

Телефон +359 2 942 45 90
Факс +359 2 942 45 91
e-mail info@bg.sika.com



EN 1504-2: 2004

14

1020

DECLARATION OF PERFORMANCE

SikaSeal[®]-210 Migrating

02	07	01	01	001	0	000249	1180
----	----	----	----	-----	---	--------	------

1. Product Type: Unique identification code of the product-type:	SikaSeal[®]-210 Migrating
2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	Batch No. see packaging
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	1-component waterproofing mortar containing migrating crystallizing additives that seal the concrete against water penetration. Surface Protection Product – coating. Intended Use – Table ZA.1e of EN 1504-2:2004. Principles 2, Methods 2.2 of EN 1504-9:2008. Conforming to the Annex ZA Table ZA.3a.
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	Sika[®] Sika CZ, s.r.o., Bystrcká 1132/36, 624 00 CZ-Brno
5. Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	Not relevant (see 4)
6. AVCP: System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	EN 1504-2:2004 → System 2+
7. Notified body (hEN): In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	Technický a zkušební ústav Praha,s.p., Prosecká 811/76a, CZ-190 00 Praha, NB no 1020. Notified factory production control certification body No. 1020 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control (FPC) 020025682.

Declaration of Performance



8. Notified body (ETA): In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:	Not relevant (refer to item 7)
--	--------------------------------

9. Declared performance

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Linear shrinkage	NPD	EN 12617-1	EN 1504-2: 2004
Coefficient of thermal expansion	NPD	EN 1770	
Adhesion by cross-cut test	NPD	EN ISO 2409	
Permeability to water vapour	Class I	EN ISO 7783-1	
Capillary absorption and permeability to water	$w < 0.1 \text{ kg}/(\text{m}^2 \times \text{h}^{0.5})$	EN 1062-3	
Adhesion after thermal compatibility	NPD	EN 13687-2	
Crack bridging ability	NPD	EN 1062-7	
Pull-off test	$\geq 1.0 (0,7) \text{ N}/\text{mm}^2$	EN 1542	
Fire Classification	A1	EN 13501-1	
Slip/skid resistance	NPD	EN 13036-4	
Artificial weathering	NPD	EN 1062-11	
Antistatic behaviour	NPD	EN 1081	
Dangerous substances	See MSDS	xxx	

NPD - No performance determined.

10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by



Ing. Jaroslav Leischner
 QMS and EHS Manager



Ing. Zdeněk Bílek, MBA
 General Manager Sika CZ

Brno, 15.04.2014



Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

REACH

European Community Regulation on chemicals and their safe use

(REACH: EC 1907/2006)

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet.

Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation, or on the candidate list published by the European Chemicals Agency in concentrations above 0.1% (w/w).

Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Sika CZ, s.r.o.
Bystrcká 1132/36,
CZ 624 00 Brno

tel: +420 546 422 464
fax: +420 546 422 400
e-mail: sika@cz.sika.com
<http://www.sika.cz>



Innovation & Consistency | since 1910